

The Comprehensive Guide to Airbus A320 Electrical Power Systems (ATA 24): Architecture, Distribution, and Fault Logic

Published: January 17, 2025 | Index ID: #922

In the domain of modern commercial aviation, the Airbus A320 family represents a milestone in technical integration, primarily due to its pioneering implementation of Fly-By-Wire (FBW) technology. Central to the success and safety of these aircraft is the **Electrical Power System (ATA 24)**. Because the A320 relies on electrical signals to actuate flight controls and maintain cockpit instrumentation, the design of the electrical system is characterized by massive redundancy, automated fault management, and high-capacity power generation. This article provides an exhaustive technical analysis of the A320's electrical architecture, covering generation, distribution, conversion, and emergency operations.

1. Philosophical Overview of the A320 Electrical Architecture

The Airbus A320 electrical system is designed around the principle of **isolated redundancy**. Unlike some older aircraft architectures that relied heavily on complex manual switching, the A320 utilizes **Generator Control Units (GCUs)** and **Bus Tie Contactors (BTCs)** to manage power distribution automatically. The primary objective is to ensure that no single failure can deprive the flight control computers of the power required to maintain the aircraft's control laws.

The system is bifurcated into two main channels: System 1 and System 2. Under normal operating conditions, these systems operate independently (split-bus operation), though they can be interconnected via a bus tie if a source fails. The system provides two types of current: **115V AC at 400Hz** (alternating current) and **28V DC** (direct current).

2. AC Generation Sources and Technical Specifications

The A320 utilizes five primary sources of AC power under various flight and ground conditions. Each source is rated to handle the entire aircraft load if necessary, though load shedding may occur in specific emergency configurations.

2.1 Main Engine Generators (IDG 1 & 2)

The primary sources of power during flight are the two **Integrated Drive Generators (IDGs)**, one mounted on each engine accessory gearbox. The IDG is a sophisticated component that combines a constant speed drive (CSD) and an oil-cooled generator into a single unit. Because engine RPM varies during different phases of flight, the CSD uses a hydro-mechanical governor to maintain a constant output frequency of **400Hz**, regardless of the N2 speed.

- Rating: 90 kVA
- Output: 115/200V, 3-phase, 400Hz
- Cooling: Dedicated oil system with an air/oil heat exchanger.

2.2 Auxiliary Power Unit (APU) Generator

The APU generator serves as a backup in flight and the primary source of power on the ground when external

power is unavailable. It is identical in rating to the engine IDGs (90 kVA), providing full redundancy. Unlike the IDGs, the APU runs at a constant speed, so it does not require a complex CSD mechanism.

2.3 External Power (EXT PWR)

Ground operations are supported by a 90 kVA external power receptacle located on the forward right side of the fuselage. The aircraft's **Ground Power Control Unit (GPCU)** monitors the quality of this power (voltage, frequency, and phase) before allowing the "EXT PWR" PB to indicate "AVAIL" and subsequently "ON."

2.4 Emergency Generation: The Ram Air Turbine (RAT)

In the event of a total loss of all main AC sources (dual engine failure or total electrical failure), a **Ram Air Turbine (RAT)** deploys automatically from the belly of the aircraft. The RAT drives a hydraulic pump, which in turn powers the **Emergency Generator (CSM/G - Constant Speed Motor/Generator)**. This unit provides 5 kVA of AC power to the essential buses, ensuring the flight crew maintains control of the aircraft and primary communications.

3. AC Distribution and Bus Tie Logic

The distribution of AC power is managed through a hierarchy of buses. The logic is programmed into the GCUs to prevent paralleling of AC sources. This means that at any given time, an AC bus can only be powered by one source.

3.1 AC Bus Priority Logic

The A320 uses a specific priority sequence for powering the main AC buses (AC BUS 1 and AC BUS 2). If the current source fails, the system automatically searches for the next available source in this order:

1. On-side Engine Generator: (e.g., Engine 1 powers AC BUS 1).
2. External Power: (If selected ON).
3. APU Generator: (If available).
4. Opposite Engine Generator: (Cross-feed via Bus Tie).

3.2 Bus Configuration Table

Bus Name	Normal Power Source	Secondary/Backup Source	Function
AC BUS 1	IDG 1	APU / EXT PWR / IDG 2	Primary AC distribution for Left-side systems
AC BUS 2	IDG 2	APU / EXT PWR / IDG 1	Primary AC distribution for Right-side systems
AC ESS BUS	AC BUS 1	AC BUS 2 / EMER GEN	Powers critical flight controls and displays
AC ESS SHED	AC ESS BUS	None (Sheds if power is limited)	Non-critical essential equipment

4. DC Generation and Conversion (The Transformer Rectifier)

While the heavy mechanical systems and primary bus distribution use AC, the avionics, sensors, and control computers require 28V DC. The A320 converts AC to DC using **Transformer Rectifiers (TRs)**. These are solid-state devices with no moving parts, converting 115V AC into 28V DC.

4.1 TR Components and Ratings

- TR 1 & TR 2: These are the primary converters, each capable of outputting 200 Amps. TR 1 is powered by AC BUS 1, and TR 2 is powered by AC BUS 2.
- ESS TR: The Essential TR is powered by the AC Essential Bus or the Emergency Generator. It ensures that even in emergency configurations, DC power remains available for flight control computers.

4.2 DC Distribution Logic

The DC system follows a similar logic to the AC system. DC BUS 1 normally powers the DC Essential Bus. However, if TR 1 fails, TR 2 can automatically take over the entire DC load. If both TR 1 and TR 2 fail, the aircraft enters a **Battery-only configuration** (if in flight) or utilizes the Essential TR if the Emergency Generator is running.

5. Energy Storage: The Battery System

The A320 is equipped with two main Nickel-Cadmium (Ni-Cd) batteries, typically rated at 23 Ah each. These batteries serve three primary purposes:

1. APU Starting: Providing the high-amperage surge required to start the APU.
2. Ground Operations: Powering the refueling panel and essential lighting when no other source is available.
3. Emergency Power: Acting as the final source of power for the DC ESS BUS and (via a Static Inverter) the AC ESS BUS during the initial stages of a total electrical failure (before the RAT deploys).

5.1 The Battery Charge Limiter (BCL)

Battery charging is managed by the **BCL**. To prevent thermal runaway (a risk with Ni-Cd batteries), the BCL monitors battery voltage and temperature. It only connects the batteries to the DC BAT BUS when charging is required. If the batteries are fully charged, they are disconnected to preserve their lifespan.

6. Technical Breakdown: The Static Inverter

A critical component often overlooked is the **Static Inverter**. In a "Battery Only" scenario (e.g., loss of all

generators and before the RAT is producing power), the aircraft must still provide 115V AC to the Essential AC Bus to keep the Captain's PFD (Primary Flight Display) and the flight control computers alive. The Static Inverter converts 28V DC from Battery 1 into 115V AC 400Hz. This output is limited (typically around 1 kVA) and is strictly for the most critical instruments.

7. Comparison Matrix: Normal vs. Emergency Power States

The following table illustrates how the electrical load is handled during various failure states.

System Component	Normal Operation	Single IDG Failure	Dual IDG Failure (RAT Extended)	Battery Only (Initial Loss)
AC BUS 1 & 2	Powered by respective IDGs	Both powered by remaining IDG	Dead (Unpowered)	Dead (Unpowered)
AC ESS BUS	Powered by AC BUS 1	Powered by AC BUS 2	Powered by EMER GEN (RAT)	Powered by Static Inverter
DC BUS 1 & 2	Powered by TR 1 & 2	Powered by remaining TR	Dead (Unpowered)	Dead (Unpowered)
DC ESS BUS	Powered by DC BUS 1	Powered by DC BUS 2	Powered by ESS TR	Powered by Batteries
Flight Displays	All displays active	All displays active	Capt PFD & ND + E/WD	Capt PFD & E/WD only

8. Troubleshooting and Operational Challenges (Case Studies)

8.1 Case Study: IDG Low Oil Pressure

A common fault in the A320 electrical system is the "ELEC IDG 1(2) OIL LO PR" ECAM warning. This indicates that the internal cooling and lubrication of the IDG is compromised. The procedure requires the pilot to disconnect the IDG. **Technical Warning:** The IDG disconnect switch must only be pressed for a maximum of 3 seconds to avoid damaging the solenoid. Furthermore, once disconnected, the IDG cannot be reconnected in flight; it requires a manual reset by maintenance on the ground. Once disconnected, the Bus Tie logic automatically switches the affected AC BUS to the APU or the opposite IDG.

8.2 Troubleshooting: Batteries Not Charging

If the "ELEC BAT 1(2) OFF" warning appears while the switches are in the AUTO position, it typically indicates a failure of the Battery Charge Limiter (BCL) or a contactor failure. On the ground, this may prevent an APU start. In flight, it reduces the emergency endurance of the aircraft. Pilots must monitor the DC BAT BUS voltage; if it drops below 25V, the battery is effectively depleted.

9. Maintenance and Ground Characteristics

The A320 maintenance manual (AMM) provides specific tolerances for the electrical system. Engineers use the **MCDU (Multipurpose Control and Display Unit)** to access the **CFDS (Centralized Fault Display System)**, which logs transient electrical faults that may not trigger a cockpit warning. For example, a minor frequency fluctuation in IDG 2 might be logged as a "Class 2" fault, allowing maintenance to replace the IDG before a full failure occurs during a revenue flight.

9.1 Transformer Rectifier (TR) Voltage/Amperage Specs

When testing TRs, technicians look for a stable output of 28V (+/- 0.5V). If the amperage on a TR exceeds 200A for an extended period, thermal protection will trip the contactor. During the engine start sequence, it is normal to see a significant jump in DC load as the FADECs (Full Authority Digital Engine Controls) and fuel pumps engage.

10. Synthesis of the System's Operational Integrity

The Airbus A320 electrical system is a masterpiece of aeronautical engineering that balances high power requirements with extreme fail-safe mechanisms. By utilizing a hierarchy of power sources—from the high-output IDGs to the emergency Static Inverter—the aircraft ensures that its digital "brain" (the ELAC, SEC, and FAC computers) never loses the power necessary to keep the aircraft within its safe flight envelope.

Understanding the interplay between the AC generation, TR conversion, and DC distribution is vital for both pilots and maintenance engineers. The system's ability to reconfigure itself in milliseconds via the Bus Tie Contactors ensures that even in complex failure scenarios, the crew's workload is minimized, and the aircraft's safety is maximized. As aviation moves toward "More Electric Aircraft" (MEA) designs, the A320's ATA 24 architecture remains the gold standard for narrow-body reliability and technical sophistication.

Baca Juga (Artikel Terkait)

- [The Definitive Technical Guide to the Lycoming O-235 Series: Engineering Architecture, Operational Performance, and Maintenance Optimization](http://alghafgolden.com/lycoming-o-235-engine-technical-guide.pdf)

URL: <http://alghafgolden.com/lycoming-o-235-engine-technical-guide.pdf>

- [The Ultimate Technical Guide to the Cessna 206 and T206 Series: Maintenance, Documentation, and Engineering Architecture](http://alghafgolden.com/cessna-206-t206-technical-maintenance-guide.pdf)

URL: <http://alghafgolden.com/cessna-206-t206-technical-maintenance-guide.pdf>

- [Comprehensive Technical Guide to Boeing 737 Maintenance Manuals: Operational Procedures and System Standards](http://alghafgolden.com/boeing-737-maintenance-manual-technical-procedures-guide.pdf)

URL: <http://alghafgolden.com/boeing-737-maintenance-manual-technical-procedures-guide.pdf>

- [Comprehensive Technical Analysis of Boeing 737 Next Generation \(NG\) Maintenance and Operational Documentation](http://alghafgolden.com/boeing-737-ng-maintenance-operations-technical-guide.pdf)

URL: <http://alghafgolden.com/boeing-737-ng-maintenance-operations-technical-guide.pdf>

Tags: #Airbus A320 #ATA 24 #Electrical Power System #Aircraft Maintenance #Avionics

